



**#192
Double-Sided
Butyl SealingTape
Product Information**

Where innovative ideas take hold.

PRODUCT DESCRIPTION

Principal Uses:

Compac #192 is typically used as a joint sealing tape (water and air) for house wrapping. Also used for sealing OSB plywood panels and flashing applications.

Features/Benefits:

- Outstanding adhesion from lower temperatures to higher temperatures.
- Excellent conformability such as in the corner of a window opening
- Excellent durability for several years usage
- Hand tearable cloth requires no tape cutting devices at the busy construction site

Please contact Technical Service for help with product and application questions at 1-877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE
Adhesive	Infrared Analysis	Butyl rubber
Adhesion to steel	PSTC-1 ASTM D3330	36 oz./ in. (39 N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	9 lb./ in. (156 N/100mm)
Thickness	PSTC-33 ASTM D3652	20 mils (0.5 mm)
Maximum performance temp.		200°F (93°C)

Application and Storage:

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

This Product Information Sheet is not intended to serve as a specification for the product; for purposes of setting specification requirements, prior agreement between Compac and the user must be established. Some values shown herein are based on measures of central tendency, and as such are considered typical or average results. Other statistical measures may be employed to determine minimum or maximum specification values. No warranty is expressed or implied with the information contained herein. Please review Compac Terms and Conditions of Sale for further information.